

The BaptistryUK baptism pool heater – 2.4kW Model with Control Box

Probably the only purpose built baptism heater on the market.
Designed to heat large baptistries of any depth.



- A 2.4kW heater to cope with baptistries up to 2400 litres (530 gals.)
- 6m flex to plug; 4m flex between element and control box.
- Built in water sensor for safety*
- Long flexes for any depth of baptism
- Stable and control box kept safely away from water
- Thermostatic control
- Element safely enclosed to prevent damage to liner
- Compact and easily stored
- Simple to use
- Runs off standard plugs - no installation costs
- Long service: we have heaters out there that are over 10 years old and going strong
- Repair and maintenance service available

Baptistry Heater



The Baptistry heater is designed to heat the water in baptistries where a hot water supply is not available.

Technical information:

One 2.4 kW heating element. The heater must NEVER be switched on outside the water. Always wait for heater to cool before removing from the water.

Heating times will vary according to the initial temperature of the water.

The 2.4 kilowatt heater comprises:

1 x 13 amp plugs
6m x PVC covered 1.25mm mains cable
4m x 6 core signal cable
ABS splash-proof control box (IP52) containing PCB
Grey PVC perforated heater box (IP68) (100mm x 170mm x 90mm) containing:
1 x 2.4 kW stainless steel elements
1 x liquid level sensor
1 x temperature sensor
with all wiring and connections encapsulated in epoxy potting compound

*Please note. It is imperative that the unit is not switched on outside water. The water sensor cannot be used as an alternative to this. The sensor is only an additional safety precaution.