

The BaptistryUK baptism pool heater – 2.4kW Model with Control Box & Thermal Cut-out

Probably the only purpose built baptistry heater on the market.
Designed to heat large baptistries of any depth.



- A 2.4kW heater to cope with baptistries up to 240 litres (530 gals.)
- 6m flex to plug; 4m flex between element and control box.
- Thermal cut-out in coil*
- Built in water sensor for safety*
- Long flexes for any depth of baptistry
- Stable and control box kept safely away from water
- Thermostatic control
- Element safely enclosed to prevent damage to liner
- Compact and easily stored
- Simple to use
- Runs off standard plugs - no installation costs
- Repair and maintenance service available

Technical information:

One 2.5 kW heating element. The heater must NEVER be switched on outside the water. Always wait for heater to cool before removing from the water.

Heating times will vary according to the initial temperature of the water.

The 2.4 kilowatt heater comprises:

1 x 13 amp plugs

6m x PVC covered 1.25mm mains cable

4m x 6 core signal cable

ABS splash-proof control box containing PCB

Grey Polypropylene perforated heater box (100mm x 170mm x 90mm) containing:

1 x 2.5 kW Incoloy elements with boil-dry cut out. If heater is switched on outside water, this will cut out and will need to be returned for resetting.

1 x liquid level sensor

1 x temperature sensor

with all wiring and connections encapsulated in epoxy potting compound

*Please note. It is imperative that the unit is not switched on outside water.